


## Rubberised magnet systems

**NdFeB magnetic system, black rubber sheath, as a complete system with hook or eyelet, rectangular**



Article number	L mm	B mm	H mm	HGes mm	Thread M	Adhesive force* N	Shear force* N	Weight g	Temp. °C	Description
AS035NDHK04S-01	35	22,5	6	30	M4	93	36	26	80	Hook
AS035NDOE04S-01	35	22,5	6	30	M4	93	36	25	80	Eyelet
AS055NDHK04S-01	55	22,5	6	30	M4	140	50	36	80	Hook
AS055NDOE04S-01	55	22,5	6	30	M4	140	50	36	80	Eyelet
AS059NDHK05S-01	59	45	8,5	40	M5	240	90	94	80	Hook
AS059NDOE05S-01	59	45	8,5	37	M5	240	90	92	80	Eyelet

### PRODUCT NOTE:

Our rectangular, **high-adhesion magnet systems** are the ideal solution for demanding applications. Internal **neodymium magnets** ensure maximum holding force. A **robust rubber coating** protects against corrosion and prevents scratches on sensitive surfaces.

**Sturdy hooks and eyelets** in various sizes provide a wide range of options for attaching or hanging objects. As a complete system, these magnetic systems are ready for immediate use in the workshop, when camping or in the trade.

As an alternative to the standard system, we also offer customised solutions:

" Other colours for the rubber coating

" Harder or softer rubber coating

<sup>1</sup> There is a cylinder bore on the holding surface due to the manufacturing process.

\* The forces have been determined at room temperature on a polished plate made of steel (S235JR according to DIN 10 025) with a thickness of 10 mm (1kg~10N). A deviation of up to -10% from the specified value is possible in exceptional cases. In general, the value is exceeded. The type of application (installation situation, temperatures, counter anchors, etc.) sometimes influence the forces enormously. The values given are for orientation purposes. Let our experts advise you.