BRUGGER MAGNETSYSTEME


PRODUCT DATA SHEET

POS magnets and hook magnets with a rubber coating

POS – NdFeB magnetic system, white rubber coating, supplied as a complete system with a hook or eyelet







PRODUCT NOTE:

Fitted with a **sturdy eyelet or hook**, this new-generation POS magnetic system offers a smart solution for a wide range of tasks. The **white rubber coating** protects surfaces from scratches and abrasion, whilst the **super-strong holding power of the neodymium magnet** ensures a reliable hold. The complete systems “Made by Brugger” are perfect for delicate materials and ensure safe and flexible use when securing or hanging objects.

Thanks to the strong neodymium magnets on the underside, our hook and eyelet magnet systems adhere securely to ferromagnetic surfaces such as metal walls, whiteboards and fridges. Organise your workspace, workshop or kitchen with our rubber-coated magnetic systems! They adhere particularly strongly to thick steel beams or directly to the housings of your machines, making them ideal for hanging tools, air guns or cleaning equipment. Our powerhouses are also perfectly suited for the hassle-free installation of control cabinets, key boxes, smoke detectors and other useful items. By the way: when camping, our white hook magnets and eyelet magnets are visually unobtrusive and ideal for attaching items directly to the bodywork of your camper van.

As an alternative to our standard range, we also offer bespoke solutions:


» **Other colours for the rubber coating**

» **Harder or softer rubber coating**

Example of use:

Rubber-coated magnet systems with hooks or eyelets are handy for attaching all sorts of objects directly to metal casings.

Gewerbestraße 23 78739 Hardt T. +49 7422 9519-0 F. +49 7422 9519-22 E. info@brugger-magnet.de



* The forces have been determined at room temperature on a polished plate made of steel (S235JR according to DIN 10 025) with a thickness of 10 mm (1kg~10N). A deviation of up to -10% from the specified value is possible in exceptional cases. In general, the value is exceeded. The type of application (installation situation, temperatures, counter anchors, etc.) sometimes influence the forces enormously. The values given are for orientation purposes. Let our experts advise you.